

V1 & V3



MORTAR PUMP FOR GUNITE AND SELFLEVELLING

TECHNICAL DATA:

	V1	V3
	ref. 0198098 2 speed	ref. 0198102 diesel
Electric connection	400 V	-
Electric motor power	6,5 – 8 Kw	22 Kw motor Diesel 4 cyl
Grain size*	0 to 10 mm	0 to 12 mm
Max. pressure	10 to 30 bar	10 to 30 bar
Output	8 - 10 m3/h	10 - 12 m3/h
Filling height	700 mm	800 mm
Dimensions LxWxH (mm)	2.300 x 700 x 700	3.300 x 1.150 x 1.200

* depends on material quality, lenth and diameter of hoses and pumping height.

V1



FEATURES AND SERIAL EQUIPMENT V1:

- 120 l hopper with low filling height.
- Robust and low maintenance costs.
- Three phase motor with protection hood.
- Remote control.
- Forward - Backward - Drive.
- Big cleaning hole.
- Easy to use and to easy to transport.
- CE certificate.
- Warranty certificate.
- Cleaning tools.
- Instruction manual and parts book.

RECOMMENDED EQUIPMENT (on order):

- 2 Speed gearbox.
- Vibrator.
- Vibrator connection.
- 2 x 20 m mortar hose 50 mm.
- 25 m electric cable.
- Spray gun (gunite).

V3



FEATURES AND SERIAL EQUIPMENT V3:

- 200 l hopper with low filling height.
- Robust and low maintenance.
- Remote control.
- Forward - Backward option.
- Big cleaning hole.
- Towable.
- Vibrator.
- CE certificate.
- Warranty certificate.
- Cleaning tools.
- Instructions manual and parts book.

RECOMMENDED EQUIPMENT (on order):

- 2 x 20 m mortar hose 50 mm.
- Spray gun (gunite).

SPARE PARTS:

Always ask for original tools and spare parts. Due to continuous improvement and development all machines can be modified without previous advice.



1. Remote control



2. 2 Speed motor



3. Electric box (73/23 CE)



4. Self levelling application



5. High pumping output



6. Selflevelling.

OUR DISTRIBUTOR: