

## Data Sheet

### The SP11 THF STAGE V Pump

Compliant with Stage V emission standard, the SP 11 THF can easily cover distances of 80 m or heights of 40 m. The sieve and vibrator have been improved to achieve a continuous material flow, even when conveying screed containing plastic or metal fibres. The maximum delivery rate of 15 m<sup>3</sup>/h and the installed equipment provide all you need to professionally convey self leveling floor screed. Wear and maintenance parts are easy to access, which makes cleaning and the replacement of wear parts more convenient. You can therefore reduce setup times and increase working productivity.

Mixing Vessel - 220 l  
Output - 0 - 15 m<sup>3</sup>/hr  
Horizontal Reach - 80 m  
Vertical Reach - 40 m  
Delivery Pressure - 20 bar  
Pump - 2L75  
Engine - 3-cylinder Kubota diesel  
Engine Power - 18.5 at 3,000 rpm kW  
Weight - 750 kg  
Length x Width x Height - 3260 x 1420 x 1160 mm  
Filling Height - 1000 mm  
Max. Aggregate Size - 8 mm  
Axle - unbraked



### Key Features

- Infinitely adjustable delivery rate
- Large hopper with safety grill - ideal to be filled by truck mixer
- Integral 100 bar high-pressure cleaner
- Large tool box (100 l)
- Central, easily adjustable support leg with low drawbar load
- Grille with vibrator for improved material flow
- Excellent soundproofing due to sound insulated engine
- Easy access makes all parts easy to service
- Extremely lightweight, impact resistant plastic hood
- CE conformity meets all safety standards in the EUy.

**Marspal House, Lawn Court, Carlton in Lindrick, Worksop, Notts, S819ED.**  
**Tel: +44 (0) 1909 730861 Email: [sales@markhampumps.co.uk](mailto:sales@markhampumps.co.uk)**  
**Website: [www.markham-sheffield.co.uk](http://www.markham-sheffield.co.uk)**