

D20

m-tec D20 Continuous Mixer

The D20 Mixer is a robust all rounder for processing dry mortar products with a granularity of up to 4 mm. It is the bestselling mixer in this class and, depending on the version, rationalizes the processing of decorative renders, bricklaying mortar or fine concrete. The 230V version specializes in the processing of decorative renders and thus is fitted with the versatile standard mixing chamber with plain bearing. It is also available in a 400V version which shows its prowess in the processing of heavy materials such as bricklaying mortar or fine concrete. In this case the ball bearing-mounted fine concrete mixing chamber is used.

The D20 is filled with bagged material as standard and offers impressively homogenous blending. The large material container is perfect for building sites. The clear layout of the controls means that the system is extremely intuitive. As is typical of all m-tec systems, the D20 has easy and quick to use connector systems that enable important elements, such as the mixing chamber or mixer motor, to be replaced in just a few seconds.



- Delivery volume: standard approx. 20 I/min (depending on the transport and mixing shaft)
- Drive motor: 2.2 kW,
 230/400 V, 50 Hz
- Weight 90kg
- Dimensions 170 x 70 x 100 cm

Lawn Road Industrial Estate, Carlton in Lindrick, Worksop, Notts, S81 9LB. England.

TEL: +44 (0) 1909 730861 FAX: +44 (0) 1909 733584 www.markham-sheffield.co.uk