

(SHEFFIELD) LTD

P20



The m-tec P20 is a compact pump for processing soft materials or pumpable products with a granularity of up to 5 mm. The P20 is mainly used to pump basic, decorative, synthetic resin and silicate renders, adhesive and reinforcing mortars, fillers or key coats.

As a 400V machine, pump P20 is fitted with a frequency converter (FU) as standard. This guarantees a powerful drive. In addition, this also enables output to be regulated continuously, so that it can be adjusted to the various products. Naturally the P20 has connections for operation with a compressor and for fully automatic feeding by means of a mixer.

The transparent layout of the controls and the conscious avoidance of superfluous switches make for easy operation. The large, stable hopper can be cleaned quickly and ensures a long service life.

The compact dimensions and lightweight design ensure problem-free transport on the building site. The large wheels, combined with the fold-out handles ensure convenient transport at all times. As is typical for m-tec, the P20 pump has very simple and quick-action locking systems that enable important elements, such as the worm pump or motor, to be replaced in just a few seconds.



- Standard delivery volume: approx. 3 22 l/min continuously adjustable (depending on the worm pump)
- Conveying distance up to 50m
- Conveying height up to 30m
- Dimensions: 115 x 58 x 54 cm
- Weight: 100kg

Lawn Road Industrial Estate, Carlton in Lindrick, Worksop, Notts, S81 9LB. England.

TEL: +44 (0) 1909 730861 FAX: +44 (0) 1909 733584

www.markham-sheffield.co.uk