

Mixer / Pump

RMX-5000

Take control of your low slump mixing, pumping, and spraying applications
Engineered to pump plaster, shotcrete, and refractories extreme distances.

Can be used for:

Refractories

High Pressure Grouting

3/8" Aggregate Shotcrete

3/8" Aggregate Concrete Mixes

Faux Rock Construction

Plaster

Stucco

Structural Panels

Slab Jacking



Blastcrete Pumps are the
most economical,
versatile, simple, and safe
concrete pumps ever built!



Anniston, AL
800-235-4867
www.blastcrete.com



Hydraulic receiving hopper lift for easy clean-out



Optional planetary gearbox for refractory applications



Compact Skid Mount Available

Features

2200 PSI Piston Face Pressure for Refractory Shotcrete and Dense Conventional Shotcrete Applications

1000 lb. Capacity Paddle Mixer with Planetary Gearbox Drive for Refractory Applications

1000 lb. Capacity Spiral Mixer for Conventional Shotcrete or Plaster Applications

Hydraulic Receiving Hopper Lift for Easy Access to Swing Tube Section for Cleaning and Maintenance

Fill Rite Water Meter

Convenient 3" HD Side Discharge

Reliable Solid State Electronics

CE Certification

Power Options

Kubota V3600 66 HP Kubota Water Cooled Diesel
50 HP Electric Motor

Specifications

	RMX-5000
Pump	3" x 18" Swing Tube
Pump Pressure	2,200 psi
Mixer	1,000 lb. Capacity
Output	0-5 Cubic YPH
Discharge	3" (side)
Hopper	1,200 lbs.
Trailer	Single 6,000 lb. Axle
Dimensions	165" x 76" x 63"
Weight	5000 lbs

Options

2,000 PSI Hydraulic Pressure Washer
Vogel Auto Lubrication System
150 ga. Water Tank with 2" Flow Meter
Spare Tire Mounted
Pendant or Wireless Remote
Skid Mounted with Forklift Tubing