Häny Mixing and Injection Technology

# High Shear Mixer



The colloidal mixer is particularly suitable for the production of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials. A robust mixing tank combined with highly wear-resistant materials in the mixing pump guarantee a long service life and trouble-free operation.



## **High Shear Mixer**

### **HCM 100**

#### Key features

#### 3D model

- ► Excellent mixing results thanks to the high turbulence generated by the high-speed mixing pump
- ► Mixing tank with conical bottom and recirculation line
- Automatic lubrication of the shaft seal and lubricated 3-way valve for switching between mixing or transfer
- Optional additional mixer for water/cement ratio
  < 0.5 and microcements</li>

#### **Typical applications**

- Preparation of suspensions consisting of water, cement, ultra-fine binder, bentonite, sand, and other materials
- As a stand-alone system or in combination with agitator and injection pump



High shear mixer		
Mixing pump:	TMP 9	_
Approx. capacity¹:	2 m³/h	_
Circulation capacity:	540 I/min	_
Usable content:	100 I	_
Max. aggregate size:	5 mm	
Liquid temperature:	Max. 40°C	_
Water connection:	BSP 3/4"	_

#### **Optional**

- Water meter 3/4" for exact water dosing (manual shut-off)
- Automatic water meter 1" with adjustable counter for exact water dosing
- Auxiliary mixing unit 3x 400/460 V, 50/60 Hz (3.0/3.6 kW)

<sup>1:</sup> Water to cement ratio = 1



Electrical data		
Voltage:	3x 400/460 V	
Frequency:	50 / 60 Hz	
Nominal power:	3.0 / 3.6 kW	
Nominal current:	6.15 / 6.45 A	
Speed:	1,440 / 1,695 min <sup>-1</sup>	

١	Weight and dimensions		
	Approx. weight:	130 kg	
	Width:	675 mm	
	Height:	1,335 mm	
	Length:	814 mm	

#### Design and dimensions





